



1	Body	A105	A182 F22	A182 F304(L)	A182 F316(L)			
2	Disc	A276 420	A276 304	A276 304(L)	A276 316(L)			
3	Stem	A182 F6	A182 F304	A182 F304(L)	A182 F316(L)			
4	Pressure seat	A105	A182 F304	A182 F304(L)	A182 F316(L)			
5	Pressure	A182 F304L			A182 F316L			
6	Bonnet	A105	A182 F22	A182 F304(L)	A182 F316(L)			
7	Pin	A276 420		A182 F304				
8	Washer	A105	A182 F22	A182 F304(L)	A182 F316(L)			
9	Lock nut	A194 2H	A194 4	A194 8	A194 8M			
10	Packing	Flexible graphite		PTFE				
11	Gland	A276 420		A182 F304				
12	Gland flange	A216 WCB		A351 CF8				
13	Gland eyebolt	A193 B7	A193 B16	A193 B8	A193 B8M			
14	Nut	A194 2H	A194 4	A194 8	A194 8M			
15	Yoke nut	A276 410						
16	Handwheel	A197						
17	Nameplate	SS						
18	Nut	A194 2H	A194 4	A194 8	A194 8M			
Suitable medium		W.O.G etc		W.O.G etc	Nitric acid,Acetic acid etc			
Suitable temperature		-29℃~425℃		-29℃~550℃	-29℃~180℃			

Note:Other material are available upon request.

CS=Carbon steel;AS=Alloy steel;SS=Stainless steel;

#### Size(MM)&Weight(KG)

NPS		1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
L(RTJ)	900Lb~ 1500Lb	216	229	254	279	305	368
	2500Lb	264	273	308	349	384	451
	900Lb~ 1500Lb	318	318	318	398	408	524
H(开)	2500Lb	333	333	333	410	420	524
	W	160	160	180	200	250	280
Weight	900Lb~ 1500Lb	15.5	16.9	18.9	28.9	34.3	52.8
	2500Lb	18	20.5	23	36.1	45	81.5